

SierraSol

BLACKOUT FABRIC

EXCLUSIVELY FROM **RollEase**®



Mesa is shown above in the Slate color to accent the room's wall color and furnishings

Mesa blackout fabric is ideal for a variety of applications that require total light blockage and privacy. Made from 100% polyester with an acrylic coating, Mesa is PVC-free, offering a high-quality, soft appearance that will add beauty to a room while reducing glare and solar heat gain.

Mesa comes in 8 popular colors to complement any décor and can be used for an array of window coverings including roller shades, Roman shades, or panel tracks. Mesa features a white backing to create a uniform appearance from the exterior.

MESA

FEATURES AND BENEFITS

PLEASING AESTHETICS

Uniquely designed to have a soft fabric appearance and feel

COLOR AVAILABILITY

Select from 8 popular colors to complement any room's décor

WHITE BACKING

Provides a uniform color to the exterior, increasing visual appeal

ACRYLIC FOAM COATING

Blackout has bounce back quality for better tracking on roll

TWO ROLL WIDTHS

Available in 98.4" and 118" roll widths to fit most large windows

FLAME RETARDANT

Certified for NFPA No. 701, California Title-19, CAN/ULC-S109

LIFETIME LIMITED WARRANTY

SierraSol is manufactured for enhanced sustainability from the best available resources

VERSATILE

Can be used on roller shades, Roman shades, or panel tracks

ENERGY SAVINGS & COMFORT

Reduces solar heat gain and glare resulting in increased energy savings and comfort

CUT YARDAGE


Conveniently order cut yardage (3 yard min.) in all colors and roll widths to make smaller jobs cost-effective




COLORS



DOVE WHITE



WHITE



PEARL



LATTE



SEAL



COCOA



SLATE



BLACK

Note: Custom color matching available. Contact RollEase for minimums and pricing.



Mesa shown above in Cocoa color

SPECIFICATIONS

COMPOSITION 100% POLYESTER WITH ACRYLIC FOAM BACKING

STANDARD ROLL WIDTHS 98.4" (2.5 M), 118" (3.0 M)

AVERAGE ROLL LENGTH 33 YD (30 M)

OPENNESS FACTOR 0% BLACKOUT

WEIGHT 9.43 OZ/YD² (320 G/M²) +/- 5%

THICKNESS 0.021" (0.55 MM) +/- 5%

YARN COUNT WARP/53 WEFT/31 (ENDS/IN)

COLORFASTNESS TO LIGHT GRADE 6-7 ISO-105-B02

TENSILE STRENGTH WARP 180, WEFT 202 daN/5CM

TEARING STRENGTH WARP 8.5, WEFT 7.85 daN

FLAME RETARDANT NFPA 701 • CALIF. TITLE-19 • CAN. ULC-S109

ENVIRONMENTAL PVC-FREE • LEAD-FREE

ENHANCED PROTECTION MOLD AND MILDEW INHIBITOR

LOW VOC EMISSION RATE <0.004 MG/M²/HR ASTM D5116

WARRANTY LIFETIME LIMITED

CLEANING WIPE CLEAN WITH WARM SOAPY WATER & DAMP CLOTH

GREENGUARD CERTIFICATION PENDING

RollEase Headquarters

200 Harvard Avenue
Stamford, CT 06902

Phone: 203-964-1573 • 800-552-5100

Order Fax: 203-358-5865

RollEase West

7310 West Roosevelt Street, Ste. 26
Phoenix, AZ 85043

Phone: 623-936-5818

Order Fax: 623-936-5294

FENESTRATION PROPERTIES

OPENNESS FACTOR 0%

UV BLOCKAGE 100%

Style	Color	Ts	Rs	As	Tv	SHADING COEFFICIENT (SC)			HEAT GAIN (G-Value)		
						1/8"CL	1/4"CL	1/4"H.A.	1/8"CL	1/4"CL	1/4"H.A.
Mesa	White*	0	76	24	0	0.22	0.23	0.26	0.19	0.20	0.23

*Similar fenestration data achieved for all other colors.

Ts = Solar Transmittance

Rs = Solar Reflectance

As = Solar Absorption

Tv = Visual Transmittance

1/8"CL = 1/8" Clear Glass

1/4"CL = 1/4" Clear Glass

1/4"H.A. = 1/4" Heat Absorbing Glass

FABRICATION METHODS: CUTTING; COLD, ULTRASONIC, CRUSH, OR LASER. SEAMING; THERMAL, HIGH FREQUENCY, ULTRASONIC, OR SEWING. RAILROADING (TURNING WIDTH FOR LENGTH) IS NOT RECOMMENDED.

THIS FABRIC IS SUITABLE FOR ROLLER SHADES, ROMAN SHADES, AND PANEL TRACKS. INTERIOR USE ONLY.

FOR SWATCH SAMPLES, CONTACT ROLLEASE CUSTOMER SERVICE 800-552-5100, FAX 203-358-5865, sales@rollease.com

COLORS MAY VARY FROM SWATCH SAMPLES. ALL VARIATIONS ARE WITHIN INDUSTRY STANDARDS. PLEASE CHECK THE COLOR BEFORE CUTTING.